

# 2" Furring Walls

WALLS

PRODUCT BROCHURE

ISSUED 2023 04 04





## UNIFY THE LOOK OF YOUR SPACE

Want to maintain a consistent aesthetic across an entire space? Easily convert rough building shell conditions to your preferred aesthetic with DIRTT's Furring Wall. Get complete customization of wall finishes and materials that fit with your overall DIRTT scope thanks to elevated fit and durability of our precision-manufactured wall assemblies. Add additional spacing to the back of the assembly to accommodate MEP or base building conditions.





## MAXIMIZE SQUARE FOOTAGE

With a slim wall assembly, our Furring Wall lets you transform your base building without sacrificing square footage. When every inch in your real estate portfolio counts, DIRTT can help you maximize your space. Barely encroaching on your floorplate, 2" Furring Walls give you full control over your aesthetic without compromising on future adaptability.





## GET THE LOOK YOU WANT

From the size of the assembly to the finishes on the panel, every aspect of a DIRTT Furring Wall is customizable. Convert your base building conditions. Conceal fire-rated construction elements with ease. Covert historical buildings without damaging existing infrastructure. DIRTT Furring Walls empower designers to unify the look of your space. And with elegant ways to integrate graphics, technology, and casework, you can express yourself while you define your space.

PRODUCT BROCHURE



2" FURRING WALLS





DIRTT Furring Walls give you the performance you need today, with the ability to adapt in the future. Wall modules can be quickly updated and reused to optimize your space. As your needs change, your space can change with you. Create a more resilient space that supports your team and your sustainability goals.





## BUILD WITH CERTAINTY

Be confident in your choices. DIRTT uses powerful software that guides the construction of our solid walls every step of the way to ensure you get what you expected without surprises. We use it to integrate your design and give you an accurate cost estimate that doesn't change after you sign off. Then it communicates with our factory to manufacture components that integrate precisely with the base building and other DIRTT systems.







## GET IN YOUR FINISHED SPACE FASTER

With industry-best lead times, DIRTT manufactures your prefabricated wall assemblies in just three weeks. Aluminum frames tip up into position quickly after the floor and ceiling are complete, reducing installation time on-site. Finished wall panels snap into place once the bulk of site work is complete, saving you time on your punch list.






## 2" Furring Wall

### SYSTEM FEATURES

	Use the Furring Wall to convert base building conditions without damaging them
01	Front side of the wall allows multiple panel configurations and finish options
02	Precision manufactured for base building accommodation
	Modular design supports quick installation and easy reconfiguration
03	Wall panels are easily removable for reducing the time and cost of maintenance
04	Leverage space in the wall cavity to integrate and protect technology
	Factory-installed recycled denim insulation provides improved acoustic performance
	SCS Indoor Advantage Gold certified

02



03



04



### Technical Overview

#### SIZE

Standard wall thickness (with panels)	2 1/8" (54 mm)
Wall module width	7 1/2" (191 mm) – 48" (1.22 m)
Wall module height maximum	12' (3.66 m)*
Factory-installed insulation thickness	1" (25 mm)

\*Frame assemblies that exceed module maximums must be validated by DIRT T to confirm they meet building code.

#### TOLERANCES

Wall height adjustability	-3/8" (10 mm) +2 3/8" (67 mm)
---------------------------	-------------------------------

#### PANEL FINISH OPTIONS

Chromacoat (paint)
ChromacoatPlus (paint)
Thermofoil (3D Laminate)
Veneer
Backpainted glass
Magnetic marker board
WriteAway (writable film)
Fabric
Custom finishes





BUILD DYNAMIC SPACES

[dirtt.com](http://dirtt.com) ↗