


Swing Doors

PRODUCT CUT SHEET





Douglas College
New Westminster, BC

Swing doors are the workhorse of any space. Strong connections to the surrounding walls and a bottom sweep create a tight seal. The door integrates seamlessly with DIRT T modular walls with precise detailing, making it the ideal choice for meeting smoke-rating requirements or acoustic needs. With both aluminum and wood options, DIRT T swing doors offer functional practicality that suits the style of your space.



SYSTEM FEATURES

- 01** Automatic door sweep creates a flush seal, ideal for sound and speech privacy
- 02** Using four butt hinges, rather than the industry standard of three, allows for higher than standard durability and quality
- 03** Aluminum door base is adjustable to accommodate base building variance
- Can be specified to meet SCS Indoor Advantage Gold certification

01



02



03



SYSTEM OPTIONS

- 04** Choose the door type that suits your aesthetic
- 05** Explore a range of standard and custom hardware, lever styles, and pulls
- Choose from regular or thin profile door types
- Use tempered or laminated glass
- Smoke-rated options available

04



05



05



Swing Doors

SIZE

Standard frame module width	40" (1.02 m)
Nominal door slab width	36" (914 mm)
Module width	variable module width available to meet clear opening requirements
Door height	as required to meet performance specifications - up to 120" (3.05 m)*

* Door assemblies that exceed module maximums must be validated by DIRT T to confirm they meet building code.

DESIGN CONFIGURATIONS

Double door
Glass or solid transom over door frame
Applied muntins on aluminum-framed glass doors

DIRTT SYSTEM INTEGRATIONS

DIRTT 4" Solid Walls
DIRTT Glass Walls
Third-party hardware

DOOR FRAME FINISH OPTIONS

Clear anodized aluminum
Powder coat
Veneer-wrapped*

COMPATIBLE DOOR HARDWARE

Locking and non-locking lever sets
Locking and non-locking pulls
Concealed closer
Flush bolt
Magnetic lock
Electric hinge

*Not applicable for Inspire™ door frames.

Third-party provided hardware



Swing Doors


SLAB TYPE

Aluminum-framed 2", 4", or 6" stile

Solid core wood

Aluminum-framed Slab

- Tempered glass option
 - Clear or low-iron
 - Optional etched finish
 - ¼" (6 mm), ⅜" (10 mm), or ½" (12 mm) glass
- Laminated glass option
 - Clear or translucent interlayer finish
 - ¼" (6 mm), ⅜" (10 mm), or ½" (12 mm) glass
- Clear anodized aluminum, powder coat, or veneer-wrapped aluminum stiles
- Regular or thin profile door types



Solid Core Wood Slab

- 1 1/8" (43 mm) solid wood
- Optional ¼" (6 mm) or ⅜" (10 mm) glass inserts
- ChromacoatPlus, Chromacoat, thermofoil, or veneer-wrapped solid slab

