





Kiewit Headquarters
Omaha, NE

Make the most of your space with quiet, smooth, and easy-to-operate sliding doors. Integrated hardware holds the door firm to the wall, making them an elegant choice for maximizing square footage. A top-mounted track offers clean lines with no obstruction, while acoustic seals help manage speech privacy. Whether you place the sliding doors inside or outside of rooms, you can customize with confidence.



Frameless Sliding Door



Thin Profile Sliding Door



Solid Core Wood Sliding Door

SYSTEM FEATURES

01	No floor track delivers on aesthetics and accessibility
02	An adjustable bottom door skirt accommodates floor variances
03	Durable soft-close and slow-down mechanisms reduce noise and extend life of the hardware
04	Non-handed design ensures minimal modifications are needed for future reconfigurations
	Can be specified to meet SCS Indoor Advantage Gold certification

01



02



03



04



SYSTEM OPTIONS

05	Explore a range of standard and custom hardware and pulls
06	Enjoy multiple design configurations, including double doors and corner door options
	Choose the door type that suits your aesthetic

05



06



Sliding Doors

SIZE	
Standard frame module width	40" (1.02 m)
Standard clear opening width	32 5⁄8" (821 mm)
Standard door slab width	40 3⁄4" (1.02 m)
Module width	variable module width available to meet clear opening requirements
Door height	as required to meet performance specifications - up to 120" (3.05 m)*
Door weight maximum	200 lbs (91 kg)
*Door assemblies that exceed module maximums must be validated by DIRT T to confirm they meet building code.	
DESIGN CONFIGURATIONS	DIRTT SYSTEM INTEGRATIONS
Double door	DIRTT 4" Solid Wall
Corner barn door	DIRTT Glass Walls
Glass or solid transom over door frame	Inspire™ Glass Walls
Applied muntins on aluminum-framed glass doors	Third-party hardware
Drywall face-mounted sliding door	
DOOR FRAME AND SLIDING DOOR TRACK FINISH OPTIONS	COMPATIBLE DOOR HARDWARE
Clear anodized aluminum	Locking and non-locking lever sets
Powder coat	Bottom locking throw [†]
Veneer-wrapped**	Floor locking pin [†]
	Magnetic lock
	Third-party provided hardware
**Not applicable for Inspire™ door frames.	
†Not applicable for frameless glass doors.	



Sliding Doors

SLAB TYPE

Frameless glass

Aluminum-framed 2", 4", or 6" stile

Solid core wood

Frameless Glass Slab

- 3/8" (10 mm) glass
- Tempered glass
- Clear or low-iron glass
- Optional etched finish



Aluminum-framed Slab

- Tempered glass option
 - Clear or low-iron
 - Optional etched finish
 - 1/4" (6 mm), 3/8" (10 mm), or 1/2" (12 mm) glass
- Laminated glass option
 - Clear or translucent interlayer finish
 - 1/4" (6 mm), 3/8" (10 mm), or 1/2" (12 mm) glass
- Clear anodized aluminum, powder coat, or veneer-wrapped aluminum stiles
- Original or thin-profile door types



Solid Core Wood Slab

- 1 1/4" (43 mm) solid wood
- Optional 1/4" (6 mm) or 3/8" (10 mm) glass inserts
- ChromacoatPlus, Chromacoat, thermofoil, or veneer-wrapped solid slab
- ChromacoatPlus, Chromacoat, thermofoil, or veneer-wrapped solid slab

